



60-100 TONNE SUPA JACK

So Safe

Lift Module shown with Load Holding Rings and Load Saddle in place



Balanced for easy manoeuvrability

Meets ASNZ Standards

Electric models available



Extensions

Load Holding Rings

Accessories



SIZING CHART



Tonnage	Stroke		Closed Height		Extend Height		4" (101mm) Base Ext		4" (101mm) Ext + 4" (101mm) Base Ext		8" (203mm) Ext + 4" (101mm) Base Ext		16" (406mm) Ext + 4" (101mm) Base Ext	
	Inches	mm	A	A	B	B	C	C	D	D	E	E	F	F
			Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
100	16	405	27	680	43	1,085	47	1,194	51	1,295	55	1,397	63	1,600
100	18	455	29	730	47	1,185	51	1,295	55	1,397	59	1,499	67	1,702
100	22	560	47	1,190	69	1,750	73	1,854	77	1,956	81	2,057	89	2,261
100	28	710	39	985	67	1,695	71	1,803	75	1,905	79	2,007	87	2,210



Tonnage	Stroke	A (inches)	A (mm)	Approx weight
100	16"/405mm	26 7/8	683	507lbs / 229kg
100	18"/455mm	28 7/8	733	550lbs / 249kg
100	22"/560mm	46 7/8	1,191	590lbs / 267kg
100	28"/710mm	38 7/8	987	620lbs / 281kg

Part number	Description
1000641	SupaJack 100T 16" Stroke - Electric
1000642	SupaJack 100T 16" Stroke - Air
1000643	SupaJack 100T 18" Stroke - Electric
1000644	SupaJack 100T 18" Stroke - Air
1000646	Load Saddle, 100T
1000648	Swivel Saddle, 100T
1000668	Load Holding Ring Set 100T 16" Stroke
1000669	Load Holding Ring Set 100T 18" Stroke
1000665	Load Holding Ring, 100T-2"
1000666	Load Holding Ring, 100T - 3"
1000667	Load Holding Rings, 100T - 5"
1000680	Extension, Steel Base 100T*
1000681	Extension Adaptor 100 Tonne - 4"
1000682	Extension Adaptor 100Tonne - 8"
1000683	Extension Adaptor, 100Tonne - 16"
1000657	Front Sus Adaptor/100T

* Required when using extensions