

HEAVY DUTY JACKING CATALOGUE

60-100 TONNE SUPA JACK

So Safe

Lift Module shown with Load Holding Rings and Load Saddle in place



Balanced for easy manoeuvrability

Meets ASNZ Standards

Air and Electric models available



Extensions

Load Holding Rings

Accessories



SIZING CHART



Tonnage	Stroke		Closed Height		Extend Height		4" (101mm) Base Ext		4" (101mm) Ext + 4" (101mm) Base Ext		8" (203mm) Ext + 4" (101mm) Base Ext		16" (406mm) Ext + 4" (101mm) Base Ext	
	Inches	mm	A	A	B	B	C	C	D	D	E	E	F	F
			Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
60	13	330	22	555	35	885	39	991	43	1,092	47	1,194	55	1,397
60	16	405	25	630	41	1,035	45	1,143	49	1,245	53	1,346	61	1,549



Tonnage	Stroke	A (inches)	A (mm)	Approx weight
60	13"/330mm	21 7/8	556	405lbs / 183kg
60	16"/405mm	24 7/8	632	447lbs / 202kg

Part number	Description
1000637	SupaJack 60T 13" Stroke - Electric
1000638	SupaJack 60T 13" Stroke - Air
1000639	SupaJack 60T 16" Stroke - Electric
1000640	SupaJack 60T 16" Stroke - Air
1000645	Load Saddle, 60 Tonne
1000647	Swivel Saddle, 60 Tonne
1000662	Load Holding Ring Set 13" Stroke
1000663	Load Holding Ring Set 16" Stroke
1000664	Load Holding Ring Set 24" Stroke
1000659	Load Holding Ring 60T - 2"
1000660	Load Holding Ring 60T - 3"
1000661	Load Holding Ring 60T - 5"
1000676	Extension, Steel Base 60T*
1000677	Extension Adaptor 60 Tonne - 4"
1000678	Extension Adaptor 60Tonne - 8"
1000679	Extension Adaptor, 60Tonne - 16"

* Required when using extensions